



| PRODUCT DETAILS | | | | |
|-----------------|----------------|------------|---------|---------------|
| NAME | The Matchmaker | SIZE: 15kg | BARCODE | 9356532010019 |

| PRODUCT OVERVIEW |
|---|
| <p>Lustre FX[®] The Matchmaker™ Quartz Primer is a water based acrylic primer for interior and exterior use on porous masonry designed to be used under the Lustre FX[®] Venetian Plaster product range.</p> <p>The Matchmaker™ fills masonry pores and any minor imperfections in the substrate, providing a sealed, anti-slip lightly textured surface, which assists the application for maximum adhesion of subsequent trowel, applied Venetian Plaster or Lustre Crete[®] products. Best applied via a 3mm nap roller or brush.</p> |

| PRECAUTIONS AND LIMITATIONS |
|---|
| <p>Spreading rates will vary from the quoted figures depending on the porosity of the substrate, surface texture, application methods and environmental conditions (e.g. wind)</p> <p>Do not apply if the surface temperature is above 40°C, or below 10°C.</p> <p>Dry times apply to a single coat at 25°C at the recommended spread rate and 50% relative humidity.</p> <p>Allow longer dry times under moist or cool conditions.</p> <p>It is the applicator's responsibility to ensure the substrate condition is of a sufficient standard to produce the subsequent specified finish. That it is free of contaminants, and any loose material is removed prior to application.</p> <p>Joint deformation or cracking of the substrate is outside the control of Lustre FX[®] control and therefore excluded from warranty terms.</p> |

| TYPICAL PROPERTIES | | | | |
|--------------------|---|------------|---|--------------------|
| V.O.C LEVEL | Not Available | CLEAN UP | Water  | |
| GLOSS LEVEL | Low sheen | THINNER | Not recommended | |
| NUMBER OF COATS | One | TOUCH DRY | 1hr | |
| APPLICATION METHOD | Paint brush or nap roller 3mm -5mm  | | | |
| COLOUR | White | | | |
| TYPICAL SYSTEM | Solids by volume 62 | | | |
| | | Min | Max | Recommended |
| | Wet film Per Coat (microns) | 51 | 76 | 51 |
| | Dry Film Per Coat (microns) | 31 | 38 | 31 |

| SPREAD RATES | | | | |
|--------------------|--------------------------------|--------------------------|----------------------------|--------------------------|
| m ² /Kg | Theoretical Spread Rate | 4m²/kg | 4.5m²/kg | 4m²/kg |

| APPLICAION GUIDE | |
|--|---|
| TYPICAL EQUIPMENT | <p>Apply with brush or roller depending on the type of texture to be overcoated. Ensure to brush or roll at the same time to the very edges of the substrate to avoid "picture framing"</p> <p>Thoroughly mix product prior to use.</p> |
| SURFACE PREPERATION <i>General guide for all surfaces</i> | <p>Previously Painted surfaces</p> <p>(a) Remove all loose or peeling paint. You can test this by cutting with a sharp blade a small X through existing paint. Press sticky tape against the cut and rip off, if the paint comes off then it unsound and should be removed. Test in a number of areas for accuracy, then wash down and sand all painted areas.</p> |

| | |
|--|---|
| | <p>(b) Fill any cracks or holes with suitable filler and sand all surfaces to a flat finish.</p> <p>Bare or Unpainted Substrates Civil Plaster: Ensure substrate is not powdery, is in good condition and sufficiently rough for good adhesion. Fibre Cement: Refer to FC manufacturer specifications with handling and working with fibre cement. DO NOT sand or cut asbestos cement. Cement Render: New render should be allowed to cure for 28 days prior to coating. Block down with a masonry rubbing stone to remove any loose surface sand, and broom for a clean surface. Brick: Suitable over porous brick, glazed bricks may not be suitable for coating and require testing first for adhesion. Tiles: For filling in grout lines and when trying to get a smooth we suggest you first use Lustre FX Base Coat</p> <p>Helpful Tips: Application of texture coatings requires protection and masking of adjoining surfaces. Use a good quality grade masking tape, mask ground areas with drop sheets, when job is finished remove the masking tape before the material sets. Ensure all areas are dust free before masking to ensure tape adhesion.</p> |
| <p>APPLCIATION PROCEDURE AND EQUIPMENT</p> | <p>Refer to the Lustre FX[®] website for a step-by-step guide and tips on applying Lustre FX[®] The Matchmaker™ Quartz Primer.</p> <p>Stirring: Stir well with a flat paddle using an up and down scooping motion. Cutting in: If using a brush apply sparingly to edges and internal angles not accessible with a roller. Feather any brushed edges. DO NOT leave thick straight edge lines as these will be visible after roller application. Roller application: Generously load the roller and apply from the ground in upward vertical strips. Helpful Tips: The first few strips will only fill the roller and less material will be applied to the substrate. Ensure successive strips deliver more product to the wall by keeping the roller wet. Apply the strips approximately ½-1m in length, reload roller after each strip and repeat until a section has been done (approximately 3-4 strips wide) Spread material evenly by rolling diagonally across the surface. Apply a fresh strip of wet material to create a “working wet edge” then “lay off”</p> |

| HEALTH AND SAFETY | |
|---|---|
| SDS(Safety Data Sheet) NUMBER | LFX007AUS |
| SDS LINK | Go to www.lustrefx.com.au for SDS downloads |
| SAFETY PRECAUTIONS | |
| Refer to the product label and current Safety Data Sheet (SDS) downloadable at www.lustrefx.com.au . | |
| HEALTH EFFECTS | IN CASE OF EMERGENCY PLEASE CALL 1800 033 111 (Australia) or 0800 734 607 (NZ) if medical advice is needed, have product container or label at hand. |
| <p>SWALLOWED: If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by mouth to an unconscious patient. Seek medical advice.</p> <p>EYE: If in eyes, hold eyes open, flood with water for at least 15 minutes and see a doctor.</p> <p>SKIN: If skin contact occurs, remove contaminated clothing and wash skin thoroughly. Continue flushing with water and if irritation occurs seek medical advice.</p> | |
| STORAGE AND DISPOSAL | |
| Store out of direct sunlight in a cool dry area. | |
| DISPOSAL | DO NOT pour down drains, refer to local regulations for the disposal of water-based waste. |

DISCLAIMER

The data provided within this PRODUCT DATA SHEET ("PDS") is correct at the time of publication, however it is the responsibility of the applicator using this information to check that it is current prior to specifying or using any of these coating systems.

Lustre FX[®], Lustre-Crete[®], and any other marks followed by [®] are registered trademarks of Lustre FX Pty Ltd ACN 638 855 704 ABN 82 638 855 704 ("LFX"). Marks followed by the symbol of [™] are trademarks.

Any advice, recommendation, information, assistance, training or service provided by LFX or its related entities in relation to goods manufactured by it or their use and application is given in good faith and believed by LFX and its related entities to be appropriate and reliable. However any advice, recommendation, information, assistance, training or service provided by LFX or its related entities is provided without liability or responsibility, provided that the foregoing shall not exclude, limit, restrict or modify the rights entitlements and remedies conferred upon any person, or the liabilities imposed upon LFX or its related entities, by any condition or warranty implied by any applicable legislation which cannot be excluded, limited or modified. Coating and product systems can be expected to perform as indicated on the PDS so long as applications and application procedures of the individual products are followed as recommended on the appropriate PDS by a qualified trained and experienced professional. The full terms and conditions of the warranty provided by LFX and its related entities (and exclusions of liability) can be downloaded at: www.lustrefx.com.au OR The full terms and conditions of the warranty provided by LFX and its related entities can be obtained by attending the office of LFX at 6 Nick Ellis Place Hume, ACT, 2620, Australia.