

PRODUCT DETAILS				
NAME	Beautiful Beast™	SIZE: 18kg	BARCODE	9356532010088

PRODUCT OVERVIEW AND USES
Lustre FX® Beautiful Beast™ Original Lustre Crete product is a classic mid grey concrete look which is mixed with water to make the workable product. Perfect for interior or exterior use for a modern concrete finish with a hand effect. Specified widely in commercial spaces, foyers, receptions, shop fit-outs, stairwells, restaurants and bespoke homes when a chic industrial style is desired. Not suitable for shower use.

Mixing guide with water:	1kg = 300ml water	18kg = 5.4Lt water
TIP: extra water can be added slowly if still too thick, if you have overwatered allow product to settle until it thickens again.		

TYPICAL SYSTEM – Based on smooth coat interior finish				
Coat	Product	Theoretical Spread rate (m ² /Kg)	Wet Film Thickness (WFT) (micron µm)	Dry Film Thickness (DFT) (micron µm)
1 st Coat	The Matchmaker™ Quartz Primer	4.5m ² /Kg	51	31
2 nd Coat	Beautiful Beast™	1.75m ² /Kg	152	143
3 rd Coat	Beautiful Beast™	2.00 m ² /Kg	152	143
4 th Coat	Top Wax Coat	20m/L	50	46.75

APPLICATION GUIDE FOR EACH COAT Based on a smooth finish
<p>1st Coat: Primer</p> <p>We recommend The Matchmaker™ Quartz Primer being applied in one coat via a roller or brush via a to give the substrate a lightly textured finish, which assists the adhesion of the subsequent Beautiful Beast™ coats. Allow to dry for 24hrs before applying the subsequent plaster coats.</p> <p>TIP: Exterior surface preparation: Prior to application ensure that the substrate is dry, clean and free from contaminants such as oil, grease, mould and fungus. Peeling debris, synthetic coatings and organic paint must first be removed and the original substrate restored prior to coating with The Matchmaker™.</p> <p>Interior surface preparation: Ensure plasterboard is not powdery, is completely dry and in good condition prior to coating with The Matchmaker™. <i>Note the primer can also be tinted to the colour of your plaster to enhance the subsequent coats if you desire.</i></p>
<p>2nd Coat: Beautiful Beast™</p> <p>Apply the first coat of Beautiful Beast™ via a trowel laying down the material as evenly as possible. DO NOT STOP as you apply pressing the trowel into the surface. Allow this coat to fully dry before laying down the next coat and finish the entire process within 24hrs.</p>
<p>3rd Coat: Beautiful Beast™</p> <p>Apply the final coat of Beautiful Beast™ when the second coat is completely dry and is where you “close down” the surface. Repeat going over the surface with hard trowel arc strokes as the product dries. At this point the product colour will deepen and the level of gloss finish is determined by the amount of polishing and hard pressing technique you put in.</p> <p>Tip: At the polishing stage thoroughly clean your trowel to ensure no rough dried plaster bits are present as this can scratch the surface.</p>

4th Coat Wax Finish: Interior surface After the surface is completely dry within 48hrs a final top wax coat can be applied to enhance the brilliance and finish. Apply wax with a soft sponge removing any excess from the surface immediately. Further enhance the gloss surface by hand polishing with a soft lint free cloth or mechanical polisher with a lambswool polishing head for a higher lustre.


Extra Coats required: Interior and Exterior use:

WE SUGGEST One or more of THE FOLLOWING EXTRA APPLICATION COATS if requiring stain proofing, hardening or water repellence.

-The Lover™ Penetrating Hardener (which densifies the concrete)

-The Therapist™ Penetrating Waterproofer (permeates deep into the surface for water and stain resistance)

-Tough As™ Polyurethane Sealer in either matt or gloss (as a top coat protector)

TYPICAL PROPERTIES				
CLEAN UP	Water 			
APPLICATION METHOD	Trowel			
APPLCIATION CONDITIONS	Solids by volume 94.34			
		Min	Max	Recommended
	Wet film Per Coat (microns)	152	178	152
	Dry Film Per Coat (microns)	143	145	143
	Recoat Time (min)	60	120	
	Theoretical Spread Rate(m²)	1.75m ² /Kg	2.00m ² /Kg	1.75m ² /Kg
COVERAGE YIELDS	Approximate average theoretical yield per bucket of 18kg of Beautiful Beast™ product is 31m²			

PRECAUTIONS AND LIMITATIONS

- Prior to application ensure that the substrate is dry, clean and free from contaminants such as oil, grease, mould and fungus. Peeling debris, paint efflorescence or any other defect that could impair adherence or the success of the application results.
- For best substrate adhesion we recommend after cleaning, to coat the substrate with The Matchmaker™ Quartz Primer.
- Apply in temperatures between 8-30 degrees C and relative humidity below 75%.
- Do not apply in the presence of strong wind, sunlight or when rain is imminent.
- Ensure you have sufficient quantity of the same batch, especially if tinted to eliminate possible batch shade variances.
- When polishing ensure your trowel is always clean and grit free to avoid scratching your surface.
- If exterior application and there is heavy rain (especially acid rain) after the first few days of application, a whitish surface deposit can occur due to the natural reaction of the calcium hydroxide that has not yet carbonised. The white deposit will lessen over time as the surface continues to get washed by rain. This is not to be considered a product defect but rather part of the natural characteristic of a mineral finish.
- If using in an EXTERIOR environment we STRONGLY RECOMMEND USING: The Lover™ Penetrating Hardener. If wanting to make the product waterproof, The Therapist™ Penetrating Waterproofer and an extra precaution and / or Tough As™(gloss or matt) Polyurethane sealer.
- If using in an INTERIOR environment such as a benchtop we STRONGLY RECOMMEND USING PART OF THIS SYSTEM TO WHAT IS RELEVANT TO THE APPLICATION: The Lover™ Penetrating Hardener, which densifies the coating. The Therapist™ Penetrating Waterproofer, for stain and water resistance. For topcoat protection, Tough As™(gloss or matt) Polyurethane sealer.

- Due to the nature of this material, the product may change appearance over time as it ages, or weathers. This is considered part of the natural beauty of the product. To slow down this process we recommend using Lustre FX® Tough As™ sealers or The Therapist™ Penetrating Waterproofer.
- NOT RECOMMENDED for use within showers.
- Lustre FX® recommends Lustre Crete products are applied by highly skilled tradespeople with extensive experience in the application of concrete or rendering products. Lustre FX® recommends that specifiers, architects, builders and clients appoint Lustre FX® trained artisans that have attended the Alchemy Academy training to ensure the same finish as any samples shown.

HEALTH AND SAFETY	
SDS(Safety Data Sheet) NUMBER	LFX 0008AUS
SDS LINK	www.lustrefx.com.au to download Safety Data Sheet
SAFETY PRECAUTIONS	
Causes skin irritation. Causes serious eye damage. May cause respiratory irritation. May cause cancer. Causes damage to organs through prolonged or repeated exposure. Keep out of reach of children. Read label before use. Do not breathe dust, fume, gas, mist, vapours or spray. Wear protective clothing, gloves, eye/face protection and suitable dust mask/respirator as required. Wash contaminated clothing before re-use. Wash hands, face and all exposed skin thoroughly after handling. Store in a well-ventilated area away from oxidising agents, acids and foodstuffs. Do not empty into drains.	
HEALTH EFFECTS	IN CASE OF EMERGENCY PLEASE CALL 1800 033 111 if medical advice is needed, have product container or label at hand.
<p>SWALLOWED: If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by mouth to an unconscious patient. Seek medical advice.</p> <p>EYE: If in eyes, hold eyes open, flood with water for at least 15 minutes and see a doctor.</p> <p>SKIN: If skin contact occurs, remove contaminated clothing and wash skin thoroughly. Continue flushing with water and if irritation occurs seek medical advice.</p> <p>INHALED: Remove patient from contaminated area. Remove contaminated clothing. Apply artificial respiration if not breathing. Seek medical advice.</p>	
TRANSPORT AND STORAGE	
Store out of direct sunlight in a cool dry area. Beautiful Beast™ product should maintain its properties for 24months if stored from excessive heat and cold temperatures.	
DISPOSAL	DO NOT pour down drains, refer to local regulations for the disposal of water-based waste. Recycle empty containers in accordance with current regulations.

DISCLAIMER

The data provided within this PRODUCT DATA SHEET ("PDS") is correct at the time of publication, however it is the responsibility of the applicator using this information to check that it is current prior to specifying or using any of these coating systems.

Lustre FX®, Lustre-Crete®, and any other marks followed by ® are registered trademarks of Lustre FX Pty Ltd ACN 638 855 704 ABN 82 638 855 704 ("LFX"). Marks followed by the symbol of ™ are trademarks.

Any advice, recommendation, information, assistance, training or service provided by LFX or its related entities in relation to goods manufactured by it or their use and application is given in good faith and believed by LFX and its related entities to be appropriate and reliable. However any advice, recommendation, information, assistance, training or service provided by LFX or its related entities is provided without liability or responsibility, provided that the foregoing shall not exclude, limit, restrict or modify the rights entitlements and remedies conferred upon any person, or the liabilities imposed upon LFX or its related entities, by any condition or warranty implied by any applicable legislation which cannot be excluded, limited or modified. Coating and product systems can be expected to perform as indicated on the PDS so long as applications and application procedures of the individual products are followed as recommended on the appropriate PDS by a qualified trained and experienced professional. The full terms and conditions of the warranty provided by LFX and its related entities (and exclusions of liability) can be downloaded at: www.lustrefx.com.au OR The full terms and conditions of the warranty provided by LFX and its related entities can be obtained by attending the office of LFX at 6 Nick Ellis Place Hume, ACT, 2620, Australia.