

### **PRODUCT DATA SHEET**

## CERA SOLIDA WAX BY TENAX™

Wax for plaster, concrete or metallic finishes

PRODUCT DETAILS				
NAME	Cera Solida Wax™	SIZE: 1L	BARCODE	9356532010484

### PRODUCT OVERVIEW AND USES

Cera Solida Wax™ is a concentrated beeswax paste formula, that penetrates into the surfaces of our Venetian Plaster or Concrete coatings. It can also be used on our metallic finishes for special effects where appropriate or other natural stones, granite, agglomerates and terrazzo.

The application can increase the polish from 5 to 15 points of gloss.

#### TYPCIAL SYSTEM

1st Coat

The Matchmaker™ Primer

2<sup>nd</sup> Coat

Any of the Lustre FX venetian plasters or concrete finishes.

3rd Coat

If applicable - any of the Lustre FX venetian plasters or concrete finishes.

4th Coat

Cera Solida Wax™

TYPICAL PROPERTIES					
CLEAN UP	Water	<b>.</b>	Number of Coats	1	
APPLICATION METHOD	Sponge, brush, roller or trowel (polish of with a cotton lint free cloth)				
COVERAGE YIELDS	Average theoretical yield 10 - 15m <sup>2</sup> /L V.O.C		<0.1		

### PRECAUTIONS AND LIMITATIONS

- Prior to application ensure that the surface is dry and all prior coats are finished and ready for final top application.
- After application of Cera Brilliant Wax it is suggested to let it permeate into the surface prior to polishing with a cotton cloth.
- Can be used for exterior applications.
- Lustre FX® recommends that specifiers, architects and builders appoint Lustre FX® trained artisans that have attended the Alchemy Academy training to ensure consistent finish to samples shown.

HEALTH AND SAFETY			
SDS(Safety Data Sheet) NUMBER	LFX0034		
SDS LINK	www.lustrefx.com.au to download Safety Data Sheet		
2D2 FIINK	www.iustreix.com.au to download Safety Data Sneet		

#### **SAFETY PRECAUTIONS**

Keep out of reach of children.

Read the label before opening or using.

Wear protective clothing, gloves, eye/face protection.

Contaminated work clothing should not be allowed out of the workplace.

Wash contaminated clothing before re-use. Wash hands, face and all exposed skin after handling.

FLAMMABILITY: Combustible liquid. Keep away from all sources of ignition - No smoking.



## **PRODUCT DATA SHEET**

# CERA SOLIDA WAX BY TENAX™

Wax for plaster, concrete or metallic finishes

**FIRST AID:** If poisoning occurs, contact a Doctor or Poisons Information Centre (Phone Australia 131 126; New Zealand 0800 764 766). If medical advice is needed, have product container or label at hand. **SWALLOWED:** If swallowed, do NOT induce vomiting. Give a glass of water. Seek medical advice.

EYE: If in eyes, hold eyes open, flood with water for at least 15 minutes and see a doctor.

**SKIN:** If skin contact occurs, remove contaminated clothing and wash skin thoroughly. Can cause skin irritation, seek medical advice if necessary.

HEALTH EFFECTS INCASE OF EMERGENCY PLEASE CALL 1800 033 111 if medical advice is needed, have product container or label at hand.

TRANSPORT AND STORAGE		
Store out of direct sunlight in a cool dry area. Cera Brilliant Wax™ product should maintain its properties		
for at least 36 months if stored away from extreme temperature variances.		
DISPOSAL	DO NOT pour down drains, refer to local regulations for the disposal of	
	chemical based waste. <b>DO NOT REUSE</b> container. Recycle empty containers in	
	accordance with current regulations.	

#### DISCI AIMER

The data provided within this PRODUCT DATA SHEET ("PDS") is correct at the time of publication, however it is the responsibility of the applicator using this information to check that it is current prior to specifying or using any of these coating systems.

Lustre FX®, Lustre-Crete®, The Alchemy Academy® and any other marks followed by ® are registered trademarks of Lustre FX Pty Ltd ACN 638 855 704 ABN 82 638 855 704 ("LFX"). Marks followed by the symbol of ™ are trademarks.

Any advice, recommendation, information, assistance, training or service provided by LFX or its related entities in relation to goods manufactured by it or their use and application is given in good faith and believed by LFX and its related entities to be appropriate and reliable. However any advice, recommendation, information, assistance, training or service provided by LFX or its related entities is provided without liability or responsibility, provided that the foregoing shall not exclude, limit, restrict or modify the rights entitlements and remedies conferred upon any person, or the liabilities imposed upon LFX or its related entities, by any condition or warranty implied by any applicable legislation which cannot be excluded, limited or modified. Coating and product systems can be expected to perform as indicated on the PDS so long as applications and application procedures of the individual products are followed as recommended on the appropriate PDS by a qualified trained and experienced professional. The full terms and conditions of the warranty provided by LFX and its related entities (and exclusions of liability) can be downloaded at: <a href="www.lustrefx.com.au">www.lustrefx.com.au</a> OR The full terms and conditions of the warranty provided by LFX and its related entities can be obtained by attending the office of LFX at 6 Nick Ellis Place Hume. ACT. 2620. Australia.